



FEATURES & SPECIFICATIONS:

Construction

- Rugged, heavy-duty die cast aluminum housing and door frame with soft corners for architectural appeal
- Hinged door frame is secured to housing with (2) tool-less latches for easy access to lamp chamber
- One-piece silicone rubber gasket provides a consistent water-tight seal
- ½" tapped holes are available for optional photocell (by others)

Optical System

- One-piece anodized aluminum reflector
- Heat and impact resistant borosilicate prismatic glass lens for even light distribution

Electrical System

- Mogul base porcelain socket, 4KV pulse rated. HID ballasts are high power factor, constant wattage autotransformer
- Recommended for ambient temperatures ranging from - 40°C to 25°C

Finish

- Standard finish is white powder coat

BSG SERIES SURFACE MOUNT HID

LISTINGS:

- UL/CUL Listed (UL 1598)
- Suitable for wet locations

APPLICATIONS:

- Canopies
- Parking areas
- Recreation areas
- Walkways
- Loading docks

SHIPPING WEIGHT:

- 33 LBS

BSG SERIES

ORDERING INFORMATION

SERIES	WATTAGE/SOURCE	VOLTAGE	OPTIONS
BSG	40P	MT	-----
SERIES BSG	WATTAGE PULSE START METAL HALIDE 17P = 175W (ED-28) 25P = 250W (ED-28) 32P = 320W (ED-28) 40P = 400W (ED-37) HIGH PRESSURE SODIUM 25S = 250W (ED-18) 40S = 400W (ED-18)	VOLTAGE MT= MULTI-TAP BALLAST (120, 208, 240, 277) 5T = 5-TAP BALLAST (120, 208, 240, 277, 480)	OPTIONS QRS= QUARTZ RESTRIKE

DIMENSIONS

