



FEATURES & SPECIFICATIONS:

Construction

- Heavy-duty die cast aluminum housing and door frame
- Hinged door frame allows for easy maintenance
- One-piece silicone gasket forms a water-tight seal between the housing and door frame
- External hardware is corrosion resistant
- Prewired with 3' #16/3 cord (Yoke mount only)
- Available with steel yoke or 2- $\frac{3}{8}$ " knuckle slipfitter painted dark bronze
- Standard finish is dark bronze powder coat

Optical System

- Heat and impact resistant tempered glass lens
- Anodized aluminum reflector system with wide, uniform beam pattern

Electrical System

- Quad-tap CWA, Class H ballasts are supplied with all metal halide fixtures and 250W & 400W high pressure sodium fixtures
- High reactance, high power factor quad-tap Class H ballast is supplied with 150W high pressure sodium
- Minimum starting temperature -40°C high pressure sodium and -30°C metal halide
- Lamp is included

LISTINGS:

- UL/CUL Listed (UL 1598)
- Suitable for wet locations

APPLICATIONS:

- Industrial yards
- Parking lots
- Walkways
- Facade Lighting
- Recreational areas
- Security
- Signage

OPTIONS:

- Wire guard
- Visor
- Polycarbonate shield

SHIPPING WEIGHT:

- 16 LBS (Yoke Mount)
- 18.5 LBS (Slipfitter Mount)


MHF SERIES

ORDERING INFORMATION


SERIES	MOUNTING	WATTAGE/SOURCE	VOLTAGE	OPTIONS
MHF	YM	40P	MT	----
SERIES MHF	MOUNTING YM = YOKE MOUNT SF = SLIPFITTER MOUNT	WATTAGE/ SOURCE PULSE START METAL HALIDE 15P = 150W (ED-28) 17P = 175W (ED-28) 25P = 250W (ED-28) 32P = 320W (ED-28) 40P = 400W (ED-28)	VOLTAGE MT = MULTI-TAP BALLAST (120, 208, 240, 277V) 5T = FIVE-TAP BALLAST (120, 208, 240, 277, 480V)	OPTIONS (FIELD INSTALLED) PS = POLYCARBONATE SHIELD VS = VISOR WG = WIRE GUARD
		HIGH PRESSURE SODIUM 15S = 150W (ED-28) 25S = 250W (ED-18) 40S = 400W (ED-18)		

MOUNTING ACCESSORIES


Mounting hardware is **not included with fixtures and must be ordered separately.



TWO FIXTURE BULLHORN




SURFACE MOUNT ADAPTER





SLIPFITTER ADAPTER

DIMENSIONS



YOKE MOUNT



SLIPFITTER MOUNT

